DIECI TELESCOPIC HANDLERS ICARUS 38.14 (93 KW) IVECO NEF F4GE0484C (2004-



2013)

| ENGINE Iveco NEF F4GE0484C Capacity: 10 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |
| Change every 400 hours | · | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |
| Change every 80 hours | | · |

| DIFFERENTIAL FRONT Capacity: 3,5 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |
| Change every 1200 hours | ' | |

| DIFFERENTIAL REAR Capacity: 3,8 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |
| Change every 1200 hours | ' | |

| HUB REDUCTIONS FRONT Capacity: 0,9 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |
| Change every 1200 hours | 1 | ' |

HYDRAULIC BRAKE SYSTEM

DIECI TELESCOPIC HANDLERS ICARUS 38.14 (93 KW) IVECO NEF F4GE0484C (2004-



2013)

| HUB REDUCTIONS REAR Capacity: 0,9 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |
| Change every 1200 hours | , | |

TRANSMISSION
Capacity: 1,5 liter

USE

Normal

PRODUCT RECOMMENDATION 2

Agrifluid Synth XHP Ultra

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30

Change every 1200 hours

| HYDRAULIC SYSTEM HYDROSTA Capacity: 160 liter | ATIC DRIVE | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus Biosynth 46 | Perlus H 46 | |
| Change every 1200 hours | | |

| Capacity: 1 liter | | |
|--------------------------|---|----------|
| USE | c | LIMATE |
| Normal | N | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |
| Change every 400 hours | | |
| USE | c | CLIMATE |
| Initial service | N | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |
| Change every 80 hours | | |

DIECI TELESCOPIC HANDLERS ICARUS 38.14 (93 KW) IVECO NEF F4GE0484C (2004-



2013)

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| COOLING SYSTEM Capacity: 7 liter | | | |
|----------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant -38 Organic NF | Coolant -26 | | |
| Change every 1200 hours | , | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.