DOOSAN (DAEWOO) FORKLIFT TRUCKS, PETROL G/GC G18S-2 MITSUBISHI G420 (2000-2007)



ENGINE Mitsubishi G420 Capacity: 4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30		
Check every 10 hours, change ever	/ 1 months/ 250 hours	·	

Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Initial service		Moderate
USE		CLIMATE

Change every 50 hours/ 1 week

DRIVE AXLE (SHOE BRAKE) Capacity: 5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

DRIVE AXLE (WET BRAKE) Capacity: 5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

TRANSMISSION Powershift Capacity: 10 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

DOOSAN (DAEWOO) FORKLIFT TRUCKS, PETROL G/GC G18S-2 MITSUBISHI G420 (2000-2007)



HYDRAULIC SYSTEM POWER STEERIN Capacity: 25 liter (Cushion), Capacity: 30 li	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	

BRAKE SYSTEM (SHOE BRAKE) Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

BRAKE SYSTEM WET BRAKES Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 15	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.