## DOOSAN (DAEWOO) FORKLIFT TRUCKS, PETROL G/GC G50SC-2 GM 4.3L V6 (1999-



2007)

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Dieselfleet MSP 10W-30	

Check every 10 hours, change every 1 months/ 250 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30	

Change every 50 hours/ 1 week

DRIVE AXLE (SHOE BRAKE) Capacity: 11,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 2000 hours/ 12 months

DRIVE AXLE (WET BRAKE) Capacity: 14 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 2000 hours/ 12 months	

TRANSMISSION Powershift		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 500 hours/ 3 months	<u>'</u>	

PRODUCT RECOMMENDATION

## DOOSAN (DAEWOO) FORKLIFT TRUCKS, PETROL G/GC G50SC-2 GM 4.3L V6 (1999-



2007)

HYDRAULIC SYSTEM POWER STEERIN Capacity: 117 liter	G	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Change every 2000 hours/ 12 months		

BRAKE SYSTEM WET BRAKES Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.