

# DOOSAN (DAEWOO) FORKLIFT TRUCKS, PETROL G/GC GC30E-3 MITSUBISHI G424 (1999-2007)



**ENGINE** Mitsubishi G424  
Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet MSP 10W-30</b>

*Check every 10 hours, change every 1 months/ 250 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet MSP 10W-30</b>

*Change every 50 hours/ 1 week*

## DIFFERENTIAL

Capacity: 10 liter (Cushion), Capacity: 9,2 liter (Pneumatic)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Multifleet SCD 10W</b>	

*Change every 2000 hours/ 12 months*

## TRANSMISSION Powershift

Capacity: 11,2 liter (Cushion), Capacity: 13 liter (Pneumatic)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Multifleet SCD 10W</b>	

*Change every 500 hours/ 3 months*

## HYDRAULIC SYSTEM POWER STEERING

Capacity: 34 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Perlus H 32</b>	

*Change every 2000 hours/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*