

# DOOSAN (DAEWOO) FORKLIFT TRUCKS, DIESEL D/GXD D33S-3 PLUS CUMMINS B3.3 (1998-2003)



**ENGINE** Cummins B3.3  
Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Check every 10 hours, change every 1 months/ 250 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Change every 50 hours/ 1 week*

**DRIVE AXLE (WET BRAKE)**  
Capacity: 9,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

*Change every 1000 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Change every 1000 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

*Change every 50 hours*

USE	CLIMATE
Initial service	Cold

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Change every 50 hours*

PRODUCT RECOMMENDATION

# DOOSAN (DAEWOO) FORKLIFT TRUCKS, DIESEL D/GXD D33S-3 PLUS CUMMINS B3.3 (1998-2003)



**TRANSMISSION** Powershift  
Capacity: 13 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1 <b>Multifleet SCD 30</b>		
--	--	--

*Change every 1000 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1 <b>Multifleet SCD 10W</b>		
---	--	--

*Change every 1000 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1 <b>Multifleet SCD 30</b>		
--	--	--

*Change every 50 hours*

USE	CLIMATE
Initial service	Cold

PRODUCT RECOMMENDATION 1 <b>Multifleet SCD 10W</b>		
---	--	--

*Change every 50 hours*



PRODUCT RECOMMENDATION

# DOOSAN (DAEWOO) FORKLIFT TRUCKS, DIESEL D/GXD D33S-3 PLUS CUMMINS B3.3 (1998-2003)



## HYDRAULIC SYSTEM POWER STEERING

Capacity: 34 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus H 68</b>	

*Change every 2500 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*Change every 2500 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus H 68</b>	

*Change every 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*Change every 1000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*