

PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX G20SC-5 MITSUBISHI G424F(E) (2007 AND AFTER)



ENGINE Mitsubishi G424
Capacity: 5,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30

Check every 10 hours, change every 1 months/ 250 hours

DRIVE AXLE (SHOE BRAKE)
Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 1 months/ 250 hours, change every 9 months/ 1500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 100 hours

DRIVE AXLE (WET BRAKE)
Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Check every 1 months/ 250 hours, change every 9 months/ 1500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 100 hours

PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX G20SC-5 MITSUBISHI G424F(E) (2007 AND AFTER)



TRANSMISSION Powershift
Capacity: 10 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
--	--	--

Check every 10 hours, change every 6 months/ 1000 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
---	--	--

Check every 10 hours, change every 6 months/ 1000 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
--	--	--

Change every 100 hours

USE	CLIMATE
Initial service	Cold

PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
---	--	--

Change every 100 hours

HYDRAULIC SYSTEM POWER STEERING

Capacity: 30 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1 Perlus H 46	PRODUCT RECOMMENDATION 2 Perlus H 68	
--	--	--

Check every 1 months/ 250 hours, change every 15 months/ 2500 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 Perlus H 32	PRODUCT RECOMMENDATION 2 Perlus H 22	
--	--	--

Check every 1 months/ 250 hours, change every 15 months/ 2500 hours

PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX G20SC-5 MITSUBISHI G424F(E) (2007 AND AFTER)



BRAKE SYSTEM (SHOE BRAKE)

Capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 1 months/ 250 hours

BRAKE SYSTEM WET BRAKES

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

Check every 1 months/ 250 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.