PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX GC30

ENGINE

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Synfleet SHPD 10W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 10W-40**

Check every 10 hours, change every 1 months/ 250 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Synfleet SHPD 10W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 10W-40**

Change every 50 hours/ 1 week

TRANSAXLE Powershift

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Change every 500 hours/ 3 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 500 hours/ 3 months

HYDRAULIC SYSTEM POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Dieselfleet CD+ 15W-40	**Multifleet SCD 10W**	

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX GC30

LIFT CHAINS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Synfleet SHPD 10W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 10W-40**

WHEEL BEARINGS

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367