DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX GC50C-5 GM G643(E)



(2007 AND AFTER)

ENGINE GM 4.3L V6 Capacity: 4,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30

Check every 10 hours, change every 1 months/ 250 hours

DRIVE AXLE (WET BRAKE) Capacity: 14 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Check every 1 months/ 250 hours,	change every 3 months/ 500 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change every 100 hours	•	

TRANSMISSION Powershift Capacity: 13 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		

Check every 10 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
Change every 100 hours	·	

DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX GC50C-5 GM G643(E)



(2007 AND AFTER)

HYDRAULIC SYSTEM POWER STEERING Capacity: 73 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus H 46	Perlus H 68		
Check every 1 months/ 250 hours, change every 15 months/ 2500 hours			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Perlus H 32			
Check every 1 months/ 250 hours, change every 15 months/ 2500 hours			

BRAKE SYSTEM WET BRAKES Capacity: 1 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 68	
Check every 1 months/ 250 hours		

Check every 1 months/ 250 hours

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	

Check every 1 months/ 250 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.