DOOSAN (DAEWOO) WHEELED LOADING SHOVEL/DOZER MEGA MEGA 160 DAEWOO DB58S (2000-2008)



ENGINE Daewoo DB58S Capacity: 13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 200 hours		·
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 50 hours		

DIFFERENTIAL FRONT Capacity: 15 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 1500 hours		
USE	CLIMATE	
Initial service	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 250 hours/ 6 months		

DIFFERENTIAL REAR Capacity: 15 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1500 hours	_
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 250 hours/ 6 months	

DOOSAN (DAEWOO) WHEELED LOADING SHOVEL/DOZER MEGA MEGA 160 DAEWOO DB58S (2000-2008)



HUB REDUCTIONS FRONT Capacity: 1,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1500 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 250 hours/ 6 months	

HUB REDUCTIONS REAR Capacity: 1,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1500 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Multifleet SHPD 15W-40	
·	
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Multifleet SHPD 15W-40	
	Multifleet SHPD 15W-40

Capacity: 20 liter

TRANSMISSION POWERSHIFT ZF 4WG130 4/3

DOOSAN (DAEWOO) WHEELED LOADING SHOVEL/DOZER MEGA MEGA 160 DAEWOO DB58S (2000-2008)



HYDRAULIC SYSTEM Capacity: 100 liter (Tank)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 2000 hours	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 29 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 1000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.