

DOOSAN (DAEWOO) TRACKED EXCAVATORS DX, DH DX300LC-3 DOOSAN DL08K (2012 AND AFTER)



ENGINE Doosan DL08K
Capacity: 36 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Change every 500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Change every 50 hours

FINAL DRIVES
Capacity: 7 liter (each)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		

Change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 1000 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		

Change every 250 hours/ 6 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 250 hours/ 6 months

DOOSAN (DAEWOO) TRACKED EXCAVATORS DX, DH DX300LC-3 DOOSAN DL08K (2012 AND AFTER)

**HYDRAULIC SYSTEM**

Capacity: 280 liter (Hydraulic tank), Capacity: 310 liter (System)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus H 68*Change every 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46

PRODUCT RECOMMENDATION 2

Perlus H 32*Change every 1000 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Change every 50 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Change every 10 hours***COOLING SYSTEM**

Capacity: 50 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

PRODUCT RECOMMENDATION 3

Coolant -33 MPG*Change every 2000 hours*

DOOSAN (DAEWOO) TRACKED EXCAVATORS DX, DH DX300LC-3 DOOSAN DL08K (2012 AND AFTER)

**SWING DRIVE UNIT**

Capacity: 6 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1 Gearlube GL-5 85W-140		
--	--	--

Change every 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
---	--	--

Change every 2000 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1 Gearlube GL-5 85W-140		
--	--	--

Change every 250 hours/ 6 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
---	--	--

Change every 250 hours/ 6 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.