

DOOSAN (DAEWOO) TRACKED EXCAVATORS DX, DH DX300SLR DOOSAN DL08 (2006-2012)



ENGINE Doosan DL08
Capacity: 36 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 2

Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 3

Agrisynth MSP 10W-40

Change every 500 hours

FINAL DRIVES

Capacity: 7 liter (each)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Change every 1000 hours

HYDRAULIC SYSTEM

Capacity: 280 liter (Hydraulic tank), Capacity: 330 liter (System)

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Perlus H 68

Change every 1000 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46

PRODUCT RECOMMENDATION 2

Perlus H 32

Change every 1000 hours

GREASE POINTS/NIPPLES

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

DOOSAN (DAEWOO) TRACKED EXCAVATORS DX, DH DX300SLR DOOSAN DL08 (2006-2012)

**COOLING SYSTEM**

Capacity: 35 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-------------------------------|--------------------------|--|
| Coolant -38 Organic NF | Coolant -26 | |

*Change every 2000 hours***SWING DRIVE UNIT**

Capacity: 6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.