

PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) TRACKED EXCAVATORS SOLAR, S-SERIES SOLAR 220 LC-V DAEWOO DB58TI (1998-2003)



ENGINE Daewoo DB58TI
Capacity: 19 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-------------------------------|-------------------------------|--|
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |

Change every 150 hours

FINAL DRIVES
Capacity: 3,3 liter (each)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 1000 hours

HYDRAULIC SYSTEM
Capacity: 220 liter (Hydraulic system including tank), Capacity: 135 liter (Hydraulic tank)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Perlus H 46 | | |

Change every 1000 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Perlus H 32 | | |

Change every 1000 hours

GREASE POINTS/NIPPLES

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------------|------------------------------|
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

DOOSAN (DAEWOO) TRACKED EXCAVATORS SOLAR, S-SERIES SOLAR 220 LC-V DAEWOO DB58TI (1998-2003)



SWING DRIVE UNIT

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.