## DOOSAN (DAEWOO) TRACKED EXCAVATORS SOLAR, S-SERIES SOLAR 250 LC-V DAEWOO D1146T (2000-2003)



| <b>ENGINE</b> Daewoo D1146T Capacity: 21 liter |                          |          |  |
|--|--------------------------|----------|--|
| USE  |                          | CLIMATE  |  |
| Normal   |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1                       | PRODUCT RECOMMENDATION 2 |          |  |
| Dieselfleet CD+ 15W-40                         | Multifleet SHPD 15W-40   |          |  |
| Change every 250 hours/ 6 months               |                          |          |  |
| USE  |                          | CLIMATE  |  |
| Initial service                                |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1                       | PRODUCT RECOMMENDATION 2 |          |  |
| Dieselfleet CD+ 15W-40                         | Multifleet SHPD 15W-40   |          |  |
| Change every 50 hours                          |                          |          |  |

| HYDRAULIC SYSTEM Capacity: 155 liter (Hydraulic tank) |               |
|---|---------------|
| USE   | CLIMATE       |
| Normal  | Mediterranean |
| PRODUCT RECOMMENDATION 1                              |               |
| Perlus H 46   |               |
| Change every 1000 hours                               |               |
| USE   | CLIMATE       |
| Normal  | Arctic        |
| PRODUCT RECOMMENDATION 1                              |               |
| Perlus H 32   |               |
| Change every 1000 hours                               |               |

| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

## DOOSAN (DAEWOO) TRACKED EXCAVATORS SOLAR, S-SERIES SOLAR 250 LC-V DAEWOO D1146T (2000-2003)



| SWING REDUCTION UNIT Capacity: 11 liter |                             |          |
|---|-----------------------------|----------|
| USE                                     |                             | CLIMATE  |
| Normal                                  |                             | Moderate |
| PRODUCT RECOMMENDATION 1                | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                    | Unigear HS GL-3/GL-5 80W-90 |          |
| Change every 1000 hours                 |                             |          |
| USE                                     |                             | CLIMATE  |
| Initial service                         |                             | Moderate |
| PRODUCT RECOMMENDATION 1                | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                    | Unigear HS GL-3/GL-5 80W-90 |          |
| Change every 250 hours/ 6 months        | ,                           |          |

| TRACK IDLERS             |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Multifleet SCD 30        |          |

| TRACK ROLLERS            |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Multifleet SCD 30        |          |

| TRAVEL REDUCTION UNIT<br>Capacity: 7 liter (each) |                             |          |
|---|-----------------------------|----------|
| USE   |                             | CLIMATE  |
| Normal  |                             | Moderate |
| PRODUCT RECOMMENDATION 1                          | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                              | Unigear HS GL-3/GL-5 80W-90 |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.