

DOOSAN (DAEWOO) SKID STEER LOADERS DSL 902 DAEWOO D430 (2000-2004)



ENGINE Daewoo D430
Capacity: 8 liter, Filter capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Change every 250 hours/ 6 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Change every 50 hours

HYDRAULIC SYSTEM
Capacity: 48 liter, Capacity: 35 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 20W-20	Multifleet SCD 10W	ATF Dexron II-D

Check every 8 hours, change every 500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 20W-20	Multifleet SCD 10W	ATF Dexron II-D

Change every 250 hours/ 6 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM
Capacity: 6,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

DOOSAN (DAEWOO) SKID STEER LOADERS DSL 902 DAEWOO D430 (2000- 2004)

**CHAIN CASE**

Capacity: 24 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 2****Synfleet SHPD 10W-40****PRODUCT RECOMMENDATION 3****Multifleet SHPD 10W-40***Change every 2000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.