

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA252 CUMMINS 4BTA 3.9C (*66120261* ->) (1998-2004)



ENGINE Cummins 4BTA3.9C
Capacity: 10 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours, change every 1 months/ 250 hours

DIFFERENTIAL REAR
Capacity: 12 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 6 months/ 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 6 months/ 1000 hours

DRUM CARTRIDGE
Capacity: 2,7 liter (each side)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Abacot MEP HD 150		

Check every 250 hours, change every 2000 hours/ 12 months

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA252 CUMMINS 4BTA 3.9C (*66120261* ->) (1998-2004)

**HUB REDUCTIONS REAR**

Capacity: 1,7 liter (each hub)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

*Check every 250 hours, change every 2000 hours/ 12 months***HYDRAULIC SYSTEM**

Capacity: 75 liter (Hydraulic system including tank), Capacity: 52 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 68		

*Check every 10 hours, change every 2000 hours/ 12 months***COOLING SYSTEM**

Capacity: 22 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA252 CUMMINS 4BTA 3.9C (*66120261* ->) (1998-2004)

**DRUM GEARBOX**

Capacity: 3 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 2000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.