DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA262 CUMMINS QSB 6.7C (67X20840 ->)



Capacity: 14 liter		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 3 months/ 500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 50 hours

DIFFERENTIAL REAR Capacity: 12 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 6 months/ 1000 hours

HUB REDUCTIONS REAR Capacity: 1,85-2 liter (each hub)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 250 hours, change ever	y 6 months/ 1000 hours	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 250 hours, change every 6	months/ 1000 hours	

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA262 CUMMINS QSB 6.7C (67X20840 ->)



HYDRAULIC SYSTEM Capacity: 75 liter (Hydraulic system including tank), Capacity: 52 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Check every 10 hours, change every 2000	hours/ 12 months	
USE		CLIMATE
Biodegradable oil		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 10 hours, change every 2000	hours/ 12 months	

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
HT Q9 High Grade Grease	Labora Grease		

COOLING SYSTEM Capacity: 29 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

ARTICULATED JOINT			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA262 CUMMINS QSB 6.7C (67X20840 ->)



DRUM Capacity: 15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 150		
Check every 250 hours, change every 2000 hours/ 12 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 150		
Change every 50 hours		

DRUM GEARBOX Capacity: 3 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 2000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.