## DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA282 D CUMMINS QSB 4.5C (10000126X0A000001 ->)



<b>ENGINE</b> Cummins QSB4.5C Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change every 3 months/ 500 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 50 hours

DIFFERENTIAL REAR Capacity: 12 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 6 months/ 1000 hours

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
Normal		Moderate
USE		CLIMATE

Check every 250 hours, change every 6 months/ 1000 hours

DRUM CARTRIDGE Capacity: 2,3 liter (each side)		
USE	c	LIMATE
Normal	N	<i>l</i> oderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 150		

Check every 250 hours, change every 2000 hours/ 12 months

## DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA282 D CUMMINS QSB 4.5C (10000126X0A000001 ->)



HUB REDUCTIONS REAR Capacity: 1,85-2 liter (each)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140		
Check every 250 hours, change every 6 months/ 1000 hours			
USE		CLIMATE	

Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 6 months/ 1000 hours

HYDRAULIC SYSTEM Capacity: 75 liter (Hydraulic system including tank), Capacity: 52 liter (Hydraulic tank)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Perlus H 68			
Check every 10 hours, change every 2000 hours/ 12 months			

USE	CLIMATE
Biodegradable oil	Mediterranean
PRODUCT RECOMMENDATION 1	
Perlus Biosynth 46	
<u>0</u>   10   10 0000	·

Check every 10 hours, change every 2000 hours/ 12 months

PRODUCT RECOMMENDATION 1 HT Q9 High Grade Grease	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
GREASE POINTS/NIPPLES		

COOLING SYSTEM Capacity: 24 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Change every 24 months			

## DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA282 D CUMMINS QSB 4.5C (10000126X0A000001 ->)



ARTICULATED JOINT			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.