

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA301/D/PD DEUTZ F6L-912 (*582*10301*)(1995-2001)



ENGINE Deutz F6L-912
Capacity: 14 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 15W-40

Check every 10 hours, change every 1 months/ 250 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 15W-40

Change every 50 hours

DIFFERENTIAL REAR
Capacity: 10,5 liter

USE
Normal

CLIMATE
Tropical

PRODUCT RECOMMENDATION 1
Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2
Unigear LS GL-3/GL-5 85W-140

Check every 250 hours, change every 2000 hours/ 12 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

Check every 250 hours, change every 2000 hours/ 12 months

HUB REDUCTIONS REAR
Capacity: 2,5 liter (each hub)

USE
Normal

CLIMATE
Tropical

PRODUCT RECOMMENDATION 1
Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2
Unigear LS GL-3/GL-5 85W-140

Check every 250 hours, change every 2000 hours/ 12 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

Check every 250 hours, change every 2000 hours/ 12 months

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA301/D/PD DEUTZ F6L-912 (*582*10301*)(1995-2001)

**HYDRAULIC SYSTEM**

Capacity: 175 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		

*Check every 10 hours, change every 2000 hours/ 12 months***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

ARTICULATED JOINT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

DRUM DRIVE UNIT

Capacity: 3 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 6 months/ 1000 hours

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA301/D/PD DEUTZ F6L-912 (*582*10301*)(1995-2001)

**PUMP DRIVE**

Capacity: 1,5 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 2000 hours/ 12 months

VIBRATION DRUM CARTRIDGE

Capacity: 26,5 liter (each side)

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 2000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.