

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA302 D/PD CUMMINS QSB 4.5 (*68X11612*->)(2012 AND AFTER)



ENGINE Cummins QSB4.5
Capacity: 11 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-------------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Check every 10 hours, change every 3 months/ 500 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-------------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Change every 50 hours

DIFFERENTIAL REAR
Capacity: 12 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|------------------------------|-------------------------------------|--|
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Check every 250 hours, change every 6 months/ 1000 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 250 hours, change every 6 months/ 1000 hours

DRUM CARTRIDGE
Capacity: 2,3 liter (each side)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Abacot MEP HD 150 | | |

Check every 250 hours, change every 2000 hours/ 12 months

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA302 D/PD CUMMINS QSB 4.5 (*68X11612*->)(2012 AND AFTER)

**HUB REDUCTIONS REAR**

Capacity: 1,85-2 liter (each hub)

| USE | | CLIMATE |
|------------------------------|-------------------------------------|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Check every 250 hours, change every 2000 hours/ 12 months

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

*Check every 250 hours, change every 2000 hours/ 12 months***HYDRAULIC SYSTEM**

Capacity: 75 liter (Hydraulic system including tank), Capacity: 52 liter (Hydraulic tank)

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 68 | | |

Check every 10 hours, change every 2000 hours/ 12 months

| USE | | CLIMATE |
|---------------------------|--|---------------|
| Biodegradable oil | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus Biosynth 46 | | |

*Check every 10 hours, change every 2000 hours/ 12 months***GREASE POINTS/NIPPLES**

| USE | | CLIMATE |
|--------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| HT Q9 High Grade Grease | Labora Grease | |

COOLING SYSTEM

Capacity: 24 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA302 D/PD CUMMINS QSB 4.5 (*68X11612*->)(2012 AND AFTER)



ARTICULATED JOINT

| USE | | CLIMATE |
|---------------------------------|------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | |

DRUM GEARBOX

Capacity: 3 liter

| USE | | CLIMATE |
|------------------------------|-------------------------------------|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Check every 250 hours, change every 2000 hours/ 12 months

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 250 hours, change every 2000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.