DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA5000 D/PD DEUTZ T4I/IIIB (10000129X0A007868 ->)



ENGINE Deutz TCD 6.1 L6 Capacity: 14 liter		
USE		CLIMATE
Alternative, fuel sulfur level < 0,0015 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Check every 10 hours, change every 500 hours/ 12 months

DIFFERENTIAL REAR Capacity: 11 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 250 hours, change every	1000 hours/ 24 months	

Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE

Check every 250 hours, change every 1000 hours/24 months

DRUM CARTRIDGE

Capacity: 2,2 liter (each side)

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS Capacity: 2 liter (each hub)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 1000 hours/24 months

Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE

Check every 250 hours, change every 1000 hours/24 months

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA5000 D/PD DEUTZ T4I/IIIB (10000129X0A007868 ->)



HYDRAI	JLIC SYST	FM
		-114

Capacity: 84 liter (Hydraulic system including tank), Capacity: 41 liter (Hydraulic tank)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Perlus H 68			
Check every 10 hours, change every 2000 hours/24 months			
USE		CLIMATE	
Biodegradable oil		Mediterranean	
PRODUCT RECOMMENDATION 1			
Perlus Biosynth 46			

Check every 10 hours, change every 2000 hours/ 24 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

COOLING SYSTEM ENGINE Capacity: 30-32,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Change every 24 months			

Change every 24 months

DYNAPAC SINGLE DRUM VIBRATORY ROLLERS CA CA5000 D/PD DEUTZ T4I/IIIB (10000129X0A007868 ->)



DRUM GEARBOX Capacity: 3,5 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 250 hours, change every 100	0 hours/ 24 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 250 hours, change every 100	0 hours/ 24 months	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Change every 50 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 50 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.