

DYNAPAC WHEELED PAVERS DF/F F1000W CUMMINS QSB-6.7 IIIB/T4I (2008) (2012 AND AFTER)



ENGINE Cummins QSB6.7C
Capacity: 17,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Check every 10 hours, change every 250 hours

PUMP REDUCTION UNIT
Capacity: 5,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 50 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM
Capacity: 189 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 2000 hours/ 12 months

USE	CLIMATE
Biodegradable oil	Mediterranean

PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 2000 hours/ 12 months

CENTRAL LUBRICATION UNIT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

DYNAPAC WHEELED PAVERS DF/F F1000W CUMMINS QSB-6.7 IIIB/T4I (2008) (2012 AND AFTER)

**COOLING SYSTEM COMBUSTION ENGINE**

Capacity: 24,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant -38 Organic NF	Coolant -26	Coolant -33 MPG

*Check every 10 hours, change every 2000 hours/ 24 months***AUGER TYPE I BEVEL GEAR**

Capacity: 0,6 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 2000 hours/ 24 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

*Change every 50 hours***CONVEYOR GEARBOX**

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 2000 hours/ 24 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 100 hours

PRODUCT RECOMMENDATION

DYNAPAC WHEELED PAVERS DF/F F1000W CUMMINS QSB-6.7 IIIB/T4I (2008) (2012 AND AFTER)



TRAVEL REDUCTION UNIT

Capacity: 3 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.