

DYNAPAC WHEELED PAVERS DF/F F161W

DEUTZ TCD2013 L04 2V (656) (2007 AND AFTER)



ENGINE Deutz TCD 2013 L04 2V
Capacity: 15 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------------|-----------------------------|--------------------------------------|
| Agrisynth LSP Ultra 10W-40 | Agrisynth LSP 10W-40 | Armado Synth LSP Ultra 10W-40 |

Check every 10 hours, change every 500 hours/ 6 months

HUB REDUCTIONS

Capacity: 2,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|---------------------------|--|
| SP Gear 1011 | Syngear TDL 75W-90 | |

Check every 50 hours, change every 1000 hours/ 12 months

PUMP REDUCTION UNIT

Capacity: 4,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 50 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 175 liter (Hydraulic tank)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Perlus H 46 | | |

Check every 10 hours, change every 2000 hours/ 24 months

| USE | CLIMATE |
|-------------------|---------------|
| Biodegradable oil | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Perlus Biosynth 46 | | |

Check every 10 hours, change every 2000 hours/ 24 months

DYNAPAC WHEELED PAVERS DF/F F161W

DEUTZ TCD2013 L04 2V (656) (2007 AND AFTER)



CENTRAL LUBRICATION UNIT

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

COOLING SYSTEM ENGINE

Capacity: 20 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

Check every 10 hours, change every 2000 hours/ 24 months

AUGER TYPE I BEVEL GEAR

Capacity: 0,6 liter (each side)

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 50 hours, change every 2000 hours/ 24 months

CONVEYOR GEARBOX

Capacity: 1,5 liter (each side)

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Abacot MEP 220 | | |

Check every 50 hours, change every 1000 hours/ 12 months

PRODUCT RECOMMENDATION

DYNAPAC WHEELED PAVERS DF/F F161W DEUTZ TCD2013 L04 2V (656) (2007 AND AFTER)



DIFFERENTIAL
Capacity: 2,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| | | |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 | | |
| Abacot MEP 220 | | |

Check every 50 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.