DYNAPAC WHEELED PAVERS DF/F F16W



| ENGINE Deutz BF6M-1012 | | |
|--------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |

Change every 120 hours

| ENGINE Deutz F6L-912 | | | |
|--------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | | |

Change every 120 hours

| | CLIMATE |
|-----------------------------|--------------------------|
| | Moderate |
| PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Jnigear HS GL-3/GL-5 80W-90 | Abacot MEP 220 |
| | |

Change every 1000 hours

| HUB REDUCTIONS | | |
|--------------------------|-----------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | Abacot MEP 220 |
| Change avery 1000 hours | | - |

Change every 1000 hours

DYNAPAC WHEELED PAVERS DF/F F16W



| HYDRAULIC SYSTEM | | |
|------------------------------------|--------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus H 68 | Perlus AF 100 | |
| Change every 2000 hours/ 24 months | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus H 46 | Perlus H 32 | |
| Change every 2000 hours/ 24 months | | |

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| CONVEYOR GEARBOX | | |
|--------------------------|-----------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | Abacot MEP 220 |
| | | |

Change every 1000 hours

| SPLITTER GEARBOX | | |
|--------------------------|-----------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | Abacot MEP 220 |
| Change even 1000 hours | | - ! |

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.