

# DYNAPAC TRACKED PAVERS DF/F/SD DF145C CUMMINS QSB6.7-C (438)



**ENGINE** Cummins QSB6.7C  
Capacity: 16,7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3             |
|-----------------------------------|-----------------------------|--------------------------------------|
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth LSP 10W-40</b> | <b>Armado Synth LSP Ultra 10W-40</b> |

*Check every 10 hours, change every 500 hours*

**PUMP REDUCTION UNIT**  
Capacity: 5,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Check every 50 hours, change every 1000 hours/ 12 months*

**HYDRAULIC SYSTEM**  
Capacity: 240 liter (Hydraulic tank)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Perlus H 46</b>       |  |  |

*Check every 10 hours, change every 2000 hours/ 24 months*

| USE               | CLIMATE       |
|-------------------|---------------|
| Biodegradable oil | Mediterranean |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Perlus Biosynth 46</b> |  |  |

*Check every 10 hours, change every 2000 hours/ 24 months*

## CENTRAL LUBRICATION UNIT

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
|--------------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

# DYNAPAC TRACKED PAVERS DF/F/SD DF145C CUMMINS QSB6.7-C (438)



## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## COOLING SYSTEM ENGINE

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Check every 10 hours, change every 2000 hours/ 24 months*

## AUGER BOX

Capacity: 5,5 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Abacot MEP 460</b>    |  |          |

*Check every 250 hours, change every 1000 hours/ 12 months*

## AUGER REDUCTION UNIT

Capacity: 0,5 liter (each side)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Abacot MEP 220</b>    |  |          |

*Check every 100 hours, change every 1000 hours/ 12 months*

## CONVEYOR GEARBOX

Capacity: 0,5 liter (each side)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Abacot MEP 220</b>    |  |          |

*Check every 250 hours, change every 1000 hours/ 12 months*

# DYNAPAC TRACKED PAVERS DF/F/SD DF145C CUMMINS QSB6.7-C (438)


**TRAVEL REDUCTION UNIT**

Capacity: 4 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Abacot MEP 220</b>    |  |          |

*Check every 250 hours, change every 1000 hours/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*