

# DYNAPAC TRACKED PAVERS DF/F/SD F4C

## DEUTZ F3L 2011 (2004-2007)



**ENGINE** Deutz F3L-2011  
Capacity: 8 liter

| USE                               |                             | CLIMATE                              |
|-----------------------------------|-----------------------------|--------------------------------------|
| Normal                            |                             | Moderate                             |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3             |
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth LSP 10W-40</b> | <b>Armado Synth LSP Ultra 10W-40</b> |

*Check every 10 hours, change every 500 hours*

**HYDRAULIC SYSTEM**  
Capacity: 70 liter (Hydraulic tank)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Perlus H 46</b>       |  |          |

*Check every 10 hours, change every 1000 hours/ 12 months*

| USE                       |  | CLIMATE       |
|---------------------------|--|---------------|
| Biodegradable oil         |  | Mediterranean |
| PRODUCT RECOMMENDATION 1  |  |               |
| <b>Perlus Biosynth 46</b> |  |               |

*Check every 10 hours, change every 1000 hours/ 12 months*

### GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

**AUGER BOX**  
Capacity: 2,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**TRAVEL REDUCTION UNIT**  
Capacity: 0,8 liter (each)

| USE                         |                          | CLIMATE  |
|-----------------------------|--------------------------|----------|
| Normal                      |                          | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2 |          |
| <b>Abacot MEP Synth 220</b> | <b>Abacot MEP 220</b>    |          |

*Check every 10 hours, change every 1500 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the*

PRODUCT RECOMMENDATION

# **DYNAPAC TRACKED PAVERS DF/F/SD F4C DEUTZ F3L 2011 (2004-2007)**



*information contained herein is subject to changes without notification.*