DYNAPAC ROLLERS CC800 89131946-> (2012 AND AFTER)



ENGINE Perkins 403D-11 Capacity: 4,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change every 500 hours/ 12 months		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 50 hours

HYDRAULIC SYSTEM Capacity: 12 liter (Hydraulic tank)		
USE	c	CLIMATE
Normal	N	Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 10 hours, change every 2000 hours/ 12 months

USE	CLIMATE
Biodegradable oil	Mediterranean
PRODUCT RECOMMENDATION 1	
Perlus Biosynth 46	

Check every 10 hours, change every 2000 hours/ 12 months

COOLING SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 500 hours/12 months	change every 24 months	1

Check every 500 hours/ 12 months, change every 24 months

DYNAPAC ROLLERS CC800 89131946-> (2012 AND AFTER)



DRUM Capacity: 3,5 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 500 hours, change ever	y 12 months/ 2000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 500 hours, change ever	y 12 months/ 2000 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.