

# DYNAPAC STATIC THREE-DRUM ROLLERS

## CS CS1400/N CUMMINS QSB 3.3

### (10000503X0A013301 ->)



**ENGINE** Cummins QSB3.3  
Capacity: 7,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40**

*Check every 10 hours, change every 1 months/ 250 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40**

*Change every 50 hours*

**HYDRAULIC SYSTEM**

Capacity: 100 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 68**

*Check every 10 hours, change every 2000 hours/ 12 months*

USE	CLIMATE
Biodegradable oil	Mediterranean

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46**

*Check every 10 hours, change every 2000 hours/ 12 months*

**GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**HT Q9 High Grade Grease**

PRODUCT RECOMMENDATION 2

**Labora Grease**

# DYNAPAC STATIC THREE-DRUM ROLLERS

## CS CS1400/N CUMMINS QSB 3.3

### (10000503X0A013301 ->)

**COOLING SYSTEM**

Capacity: 19 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Check every 10 hours, change every 2000 hours/ 24 months

**ARTICULATED JOINT**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*