

DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC122C DEUTZ D2011- L02I (10000308X0A000001 ->)



ENGINE Deutz D 2011 L02i
Capacity: 6,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40

Check every 10 hours, change every 3 months/ 500 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40

Change every 50 hours

HYDRAULIC SYSTEM

Capacity: 40 liter (Hydraulic tank)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Perlus H 68

Check every 10 hours, change every 2000 hours/ 12 months

USE
Biodegradable oil

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46

Check every 10 hours, change every 2000 hours/ 12 months

GREASE POINTS/NIPPLES

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease

PRODUCT RECOMMENDATION 2

Labora Grease

DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC122C DEUTZ D2011- L02I (10000308X0A000001 ->)

**DRUM**

Capacity: 4 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.