DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC21 SERIES 2 JOHN DEERE 4239 DF (476 004 ->)



ENGINE John Deere 4239 DF Capacity: 8,5 liter, Filter capacity: 0,9 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		
Change every 100 hours		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 100 hours		
USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		
Change every 50 hours		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 50 hours		
DRUM GEARBOX FRONT		
		CLIMATE
use Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 1 months/ 200 hours, change every 6 months/ 1000 hours

use Initial service		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 200 hours		

DYNAPAC TANDEM DRUM VIBRATORY **ROLLERS CC/CG/LA CC21 SERIES 2 JOHN** DEERE 4239 DF (476 004 ->)



DRUM GEARBOX REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check even 1 months/200 hours change	$\frac{1}{1000}$ every 6 months/ 1000 hours	·

Check every 1 months/ 200 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 200 hours

PUMP REDUCTION UNIT Capacity: 1,5-3,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
		· ·

Check every 200 hours, change every 12 months/ 2000 hours

HYDRAULIC SYSTEM Capacity: 140 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Check evenu 10 hours, change evenu 2000 hours/ 12 months		

Check every 10 hours, change every 2000 hours/ 12 months

DRUM FRONT Capacity: 20 liter		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 50 hours, change ever	y 12 months/ 2000 hours	•

DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC21 SERIES 2 JOHN DEERE 4239 DF (476 004 ->)



DRUM REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 50 hours, change every 12 months/ 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.