

PRODUCT RECOMMENDATION

# DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC221 DEUTZ F4L-912 (\*61510222\* ->)



**ENGINE** Deutz F4L-912  
Capacity: 11 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 50 hours*

**HYDRAULIC SYSTEM**  
Capacity: 140 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Perlus H 68</b>		

*Check every 1 months/ 250 hours, change every 12 months/ 2000 hours*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

# DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC221 DEUTZ F4L-912 (\*61510222\* ->)



## DRUM

Capacity: 20 liter

### USE

Normal

### CLIMATE

Tropical

#### PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140**

#### PRODUCT RECOMMENDATION 2

**Unigear LS GL-3/GL-5 85W-140**

*Check every 1 months/ 250 hours, change every 12 months/ 2000 hours*

### USE

Normal

### CLIMATE

Moderate

#### PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

#### PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 1 months/ 250 hours, change every 12 months/ 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*