DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC334HF DEUTZ TCD3.6 L04 T4I/IIIB (10000338X0A011354 ->)



ENGINE Deutz TCD 3.6 L4 Capacity: 8 liter USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Agrisynth MSP 10W-40 Agridiesel MSP 15W-40 Dieselfleet MSP 15W-40 Check every 10 hours, change every 500 + burs/ 6 months CLIMATE

| Agrisynth MSP 10W-40 | Agridiesel MSP 15W-40 | Dieselfleet MSP 15W-40 |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Initial service | | Moderate |

Change every 50 hours

| HYDRAULIC SYSTEM Capacity: 40 liter (Hydraulic tank) | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 68 | | |
| Check every 10 hours, change every 2000 hours/ 12 months | | |

| USE | | CLIMATE |
|--|--|---------------|
| Biodegradable oil | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus Biosynth 46 | | |
| Check every 10 hours, change every 2000 hours/ 12 months | | |

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| HT Q9 High Grade Grease | Labora Grease | |

DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC334HF DEUTZ TCD3.6 L04 T4I/IIIB (10000338X0A011354 ->)



| Coolant -38 Organic NF | Coolant -26 | | |
|---|--------------------------|----------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Normal | | Moderate | |
| USE | | CLIMATE | |
| COOLING SYSTEM Capacity: 18,9-20,1 liter | | | |

Change every 24 months

| DRUM Capacity: 9 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Abacot MEP HD 150 | | |
| Charles ware 2 martha/ 500 hours charge avery 6 martha/ 1000 hours | | |

Check every 3 months/ 500 hours, change every 6 months/ 1000 hours

| DRUM GEARBOX Capacity: 1,7 liter | | |
|-------------------------------------|------------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Check every 50 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|---|-----------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Check war 50 hours change over 0 months/ 4000 hours | | |

Check every 50 hours, change every 6 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.