

DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC4200 (97 KW) CUMMINS QSB 4.5 IIB/T4I

**ENGINE Cummins QSB4.5 (IIB/T4I)**

Capacity: 11 liter

USE	CLIMATE
Normal, fuel sulfur level <15 ppm	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 2

Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 3

Dieselfleet MSP 15W-40*Check every 10 hours, change every 500 hours/ 6 months***HYDRAULIC SYSTEM**

Capacity: 40 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46*Check every 10 hours, change every 2000 hours/ 12 months*

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 68*Check every 10 hours, change every 2000 hours/ 12 months***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease

PRODUCT RECOMMENDATION 2

Labora Grease**COOLING SYSTEM**

Capacity: 21,4-23,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Change every 24 months***DRUM**

Capacity: 14 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

PRODUCT RECOMMENDATION

DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC4200 (97 KW) CUMMINS QSB 4.5 IIIB/T4I



DRUM LUBRICANT

Capacity: 1,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 50 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 50 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 50 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.