

# DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC422VHF CUMMINS 4BTAA 3.9C (\*49720423\* ->) (2003-2008)



**ENGINE** Cummins 4BTAA 3.9C  
Capacity: 11 liter

**USE**  
Normal

**CLIMATE**  
Mediterranean

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40**

*Check every 10 hours, change every 3 months/ 500 hours*

**USE**  
Initial service

**CLIMATE**  
Mediterranean

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40**

*Change every 50 hours*

**PUMP REDUCTION UNIT**  
Capacity: 0,8 liter

**USE**  
Normal

**CLIMATE**  
Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 50 hours, change every 6 months/ 1000 hours*

**HYDRAULIC SYSTEM**  
Capacity: 40 liter

**USE**  
Normal

**CLIMATE**  
Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 68**

*Check every 10 hours, change every 2000 hours/ 12 months*

**USE**  
Biodegradable oil

**CLIMATE**  
Mediterranean

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46**

*Check every 10 hours, change every 2000 hours/ 12 months*

# DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC422VHF CUMMINS 4BTAA 3.9C (\*49720423\* ->) (2003-2008)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

## COOLING SYSTEM

Capacity: 7,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 2000 hours/ 24 months

## ARTICULATED JOINT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Change every 50 hours

## DRUM

Capacity: 14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 150		

Check every 3 months/ 500 hours, change every 6 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.