

DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA LA90 HATZ 2G30 (1988- 1993)



ENGINE Hatz 2G30
Capacity: 3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-------------------------------|-------------------------------|
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Change every 200 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-------------------------------|-------------------------------|
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Change every 50 hours

HYDRAULIC SYSTEM
Capacity: 30 liter (Hydraulic tank)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------|--|
| Perlus H 68 | |

Check every 10 hours, change every 6 months/ 1000 hours

GREASE POINTS/NIPPLES

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|-------------------------------|
| Labora Grease | Multi Purpose Grease 3 |

DRUM BEARINGS

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|-------------------------------|
| Labora Grease | Multi Purpose Grease 3 |

DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA LA90 HATZ 2G30 (1988- 1993)



OIL CAN LUBRICATION

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 68 | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.