DYNAPAC PNEUMATIC TYRED ROLLERS CP CP142 CUMMINS QSB 3.3 (*2163BR3001* ->)



ENGINE Cummins QSB3.3 Capacity: 9,5 liter			
use Normal		CLIMATE	
		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every	3 months/ 500 hours		
USE		CLIMATE	

Initial service

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

Multifleet SHPD 15W-40

Change every 50 hours

HYDRAULIC SYSTEM Capacity: 100 liter (Hydraulic system incl	uding tank), Capacity: 75 liter (Hydraulic tank		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Perlus H 68			
Check every 10 hours, change every 200	0 hours/ 12 months		
USE		CLIMATE	
Biodegradable oil		Mediterranean	

Biodegradable oil	Mediterranean
PRODUCT RECOMMENDATION 1	
Perlus Biosynth 46	
Check every 10 hours, change every 2000	hours/12 months

Check every 10 hours, change every 2000 hours/ 12 months

	CLIMATE	
	Moderate	
PRODUCT RECOMMENDATION 2		
Labora Grease		
		PRODUCT RECOMMENDATION 2

DYNAPAC PNEUMATIC TYRED ROLLERS CP CP142 CUMMINS QSB 3.3 (*2163BR3001* ->)



COOLING SYSTEM Capacity: 20 liter CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Coolant -38 Organic NF Coolant -26

Check every 10 hours, change every 2000 hours/24 months

ARTICULATED JOINT			
use Normal		climate Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.