

EAGLE TUGS TRANSIT SERIES TT TT-4

LPG WISCON TM27 (2009 AND AFTER)

**ENGINE** Wisconsin TM27

Capacity: 6,65 liter, Filter capacity: 0,95 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-----------------------------|-------------------------------|
| Kroontrak MTH 10W-30 | Multifleet SHPD 10W-40 |

Check every 8 hours, change every 100 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-----------------------------|-------------------------------|
| Kroontrak MTH 10W-30 | Multifleet SHPD 10W-40 |

*Check every 8 hours, change every 50 hours***DIFFERENTIAL FRONT**

Capacity: 2,48 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-----------------------------|------------------------------------|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 |

*Change every 1000 hours/ 12 months***DIFFERENTIAL REAR**

Capacity: 3,75 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-----------------------------|------------------------------------|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 |

*Change every 1000 hours/ 12 months***TRANSMISSION POWERSHIFT 3/1**

Capacity: 3,8 liter (Change capacity), Capacity: 4,25 liter (Torque converter), Capacity: 8,05 liter (Total)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|--------------------------|
| SP Matic 2032 | ATF Almirol |

Change every 1000 hours/ 12 months

EAGLE TUGS TRANSIT SERIES TT TT-4

LPG WISCON TM27 (2009 AND AFTER)



HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 3 | | |

Check every 250 hours

POWER STEERING

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 2032 | | |

Change every 1000 hours/ 12 months

COOLING SYSTEM

Capacity: 15,1 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant -38 Organic NF | Coolant -26 | Coolant -33 MPG |

Check every 250 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.