

# ETEC WHEELED LOADERS 2025-II

## DOOSAN DL06



**ENGINE** Doosan DL06  
Capacity: 27 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Agrisynth LSP Ultra 10W-40**

PRODUCT RECOMMENDATION 2

**Agrisynth LSP 10W-40**

PRODUCT RECOMMENDATION 3

**Agrisynth MSP 10W-40**

*Change every 500 hours*

**DIFFERENTIAL FRONT**  
Capacity: 31 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**DIFFERENTIAL REAR**  
Capacity: 24 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**TRANSMISSION**  
Capacity: 45 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40**

*Change every 1000 hours*

**HYDRAULIC SYSTEM**  
Capacity: 158 liter (Hydraulic tank)

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 46**

*Change every 2000 hours*

### GREASE POINTS/NIPPLES

USE  
Normal

CLIMATE  
Mediterranean

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

# ETEC WHEELED LOADERS 2025-II

## DOOSAN DL06



### COOLING SYSTEM

Capacity: 45 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Change every 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*