PRODUCT RECOMMENDATION

ETEC TRACKED EXCAVATORS 806-II R

ENGINE Yanmar 4TNV98-Z
Capacity: 11,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrisynth LSP Ultra 10W-40	**Agrisynth LSP 10W-40**	**Agrisynth MSP 10W-40**

Change every 500 hours

HYDRAULIC SYSTEM
Capacity: 72 liter (Hydraulic tank), Capacity: 108 liter (Total)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Perlus H 68	**Perlus AF 68**	

Change every 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Perlus H 46	**Perlus H 32**	**Perlus AF 46**

Change every 1000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

COOLING SYSTEM
Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Coolant -38 Organic NF	**Coolant -26**	

Change every 2000 hours

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Coolant -38 Organic NF	**Coolant -26**	

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

ETEC TRACKED EXCAVATORS 806-II R

TRAVEL REDUCTION UNIT Capacity: 1,4 liter		
USE Normal		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1 **Gearlube GL-5 85W-140**		
Change every 500 hours		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Gearlube GL-5 80W-90**	PRODUCT RECOMMENDATION 2 **Unigear HS GL-3/GL-5 80W-90**	
Change every 500 hours		
USE Initial service		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1 **Gearlube GL-5 85W-140**		
Change every 500 hours		
USE Initial service		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Gearlube GL-5 80W-90**	PRODUCT RECOMMENDATION 2 **Unigear HS GL-3/GL-5 80W-90**	
Change every 500 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367