## EUROCOMACH TRACKED EXCAVATORS ES 28ZT KUBOTA D1503-M (S/N DB 00051 -



**>)** (2012 AND AFTER)

ENGINE Kubota D1503-M Capacity: 7 liter		
JSE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 250 hours		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20		
Change every 250 hours	'	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Asyntho 5W-30	Armado Synth 5W-30
Change every 250 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 250 hours		
JSE		CLIMATE
Initial service		Tropical
Multifleet SCD 30		
Change every 50 hours		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
		·
Change every 50 hours		
Change every 50 hours		CLIMATE
		CLIMATE Moderate
USE	PRODUCT RECOMMENDATION 2	

## EUROCOMACH TRACKED EXCAVATORS ES 28ZT KUBOTA D1503-M (S/N DB 00051 -



>) (2012 AND AFTER)

USE	CLIMATE
Initial service	Arctic
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 50 hours	

HYDRAULIC SYSTEM
Capacity: 54 liter (Hydraulic system including tank), Capacity: 30 liter (Hydraulic tank)

use
CLIMATE
Normal
Moderate

PRODUCT RECOMMENDATION 1
Perlus Biosynth 46
Perlus H 46

Change every 1000 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 7,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Change every 24 months			

Normal	PRODUCT PERCHAPITATION O	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

## EUROCOMACH TRACKED EXCAVATORS ES 28ZT KUBOTA D1503-M (S/N DB 00051 -



>) (2012 AND AFTER)

TRAVEL REDUCTION UNIT Capacity: 1 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.