

EUROCOMACH TRACKED EXCAVATORS

ES 35ZT KUBOTA D1503-M (S/N CT 00051 ->)

(2012 AND AFTER)



ENGINE Kubota D1503-M
Capacity: 7 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 250 hours*

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20*Change every 250 hours*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Asyntho 5W-30

PRODUCT RECOMMENDATION 3

Armado Synth 5W-30*Change every 250 hours*

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 250 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Tropical |

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 50 hours*

| USE | CLIMATE |
|-----------------|---------------|
| Initial service | Mediterranean |

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20*Change every 50 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Asyntho 5W-30

PRODUCT RECOMMENDATION 3

Armado Synth 5W-30*Change every 50 hours*

EUROCOMACH TRACKED EXCAVATORS

ES 35ZT KUBOTA D1503-M (S/N CT 00051 ->)

(2012 AND AFTER)



| USE | | CLIMATE |
|------------------------------|--|---------|
| Initial service | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |
| <i>Change every 50 hours</i> | | |

| HYDRAULIC SYSTEM | | |
|---|--------------------------|----------|
| Capacity: 54 liter (Hydraulic system including tank), Capacity: 30 liter (Hydraulic tank) | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus Biosynth 46 | Perlus H 46 | |
| <i>Change every 1000 hours</i> | | |

| GREASE POINTS/NIPPLES | | |
|--------------------------|---------------------------------|------------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| COOLING SYSTEM | | |
|-------------------------------|--------------------------|----------|
| Capacity: 7,5 liter | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |
| <i>Change every 24 months</i> | | |

| TRACK TENSIONERS | | |
|--------------------------|---------------------------------|------------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |



EUROCOMACH TRACKED EXCAVATORS

ES 35ZT KUBOTA D1503-M (S/N CT 00051 ->)

(2012 AND AFTER)

**TRAVEL REDUCTION UNIT**

Capacity: 1 liter (each)

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.