

EUROCOMACH TRACKED EXCAVATORS

ES 500 ISUZU 4LE1 PA-03



ENGINE Isuzu 4LE1PA-03
Capacity: 8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-------------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Change every 250 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-------------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Change every 50 hours

HYDRAULIC SYSTEM
Capacity: 60 liter (Hydraulic tank)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---------------------------|--------------------------|--|
| Perlus Biosynth 46 | Perlus H 46 | |

Check every 8 hours, change every 2000 hours

GREASE POINTS/NIPPLES

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------------|------------------------------|
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 8 hours

COOLING SYSTEM

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-------------------------------|--------------------------|--|
| Coolant -38 Organic NF | Coolant -26 | |

Check every 8 hours, change every 6 months/ 500 hours

EUROCOMACH TRACKED EXCAVATORS

ES 500 ISUZU 4LE1 PA-03



TRACK CARRIER ROLLER

Capacity: 0,07 liter (each)

| USE | | CLIMATE |
|------------------------------|-------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Change every 1000 hours

TRACK FRONT ROLLER

Capacity: 0,07 liter (each)

| USE | | CLIMATE |
|------------------------------|-------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Change every 2000 hours

TRACK LOWER IDLER

Capacity: 0,08 liter (each)

| USE | | CLIMATE |
|------------------------------|-------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Change every 1000 hours

TRAVEL REDUCTION UNIT

Capacity: 0,8 liter

| USE | | CLIMATE |
|------------------------------|-------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Change every 1000 hours

| USE | | CLIMATE |
|------------------------------|-------------------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Change every 500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.