## FUCHS ARTICULATED LOADERS F1100 YANMAR 3TNV88 (2007-2014)



| ENGINE Yanmar 3TNV88 Capacity: 6,7 liter   |   |   |
|--|---|---|
| JSE  |   | CLIMATE                                   |
| Normal   |   | Tropical                                  |
| PRODUCT RECOMMENDATION 1   |   |   |
| Multifleet SCD 40  |   |   |
| Change every 250 hours   | '   | ,   |
| USE  |   | CLIMATE                                   |
| Normal   |   | Mediterranean                             |
| PRODUCT RECOMMENDATION 1   |   |   |
| Multifleet SCD 30  |   |   |
| Change every 250 hours   |   |   |
| USE  |   | CLIMATE                                   |
| Normal   |   | Moderate                                  |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2                      | PRODUCT RECOMMENDATION 3                  |
| Kroontrak MTH 10W-30   | Synfleet SHPD 10W-40                          | Dieselfleet CD+ 15W-40                    |
| Change every 250 hours   |   |   |
| USE  |   | CLIMATE                                   |
| Normal   |   | Cold                                      |
|  |   |   |
| PRODUCT RECOMMENDATION 1   |   |   |
| PRODUCT RECOMMENDATION 1   |   |   |
| PRODUCT RECOMMENDATION 1  Multifleet SCD 10W   |   |   |
| Multifleet SCD 10W  Change every 250 hours   |   | CLIMATE                                   |
| Multifleet SCD 10W  Change every 250 hours   |   | climate<br>Tropical                       |
| PRODUCT RECOMMENDATION 1  Multifleet SCD 10W  Change every 250 hours  USE  Initial service  PRODUCT RECOMMENDATION 1   |   |   |
| Multifleet SCD 10W  Change every 250 hours  USE Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 40   |   |   |
| Multifleet SCD 10W  Change every 250 hours  use Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  |   |   |
| Multifleet SCD 10W  Change every 250 hours  USE Initial service PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  |   | ССІМАТЕ                                   |
| Multifleet SCD 10W  Change every 250 hours  USE Initial service PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE Initial service  |   | Tropical                                  |
| Multifleet SCD 10W  Change every 250 hours  USE Initial service PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE Initial service PRODUCT RECOMMENDATION 1   |   | ССІМАТЕ                                   |
| Multifleet SCD 10W  Change every 250 hours  USE Initial service PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE Initial service PRODUCT RECOMMENDATION 1  Multifleet SCD 30  |   | ССІМАТЕ                                   |
| Multifleet SCD 10W  Change every 250 hours  USE Initial Service PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE Initial Service PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 50 hours   |   | ССІМАТЕ                                   |
| Multifleet SCD 10W  Change every 250 hours  USE Initial service PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE Initial service PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 50 hours   |   | Tropical  CLIMATE  Mediterranean  CLIMATE |
| Multifleet SCD 10W  Change every 250 hours  USE Initial Service PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE Initial Service PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 50 hours  USE Initial Service PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 50 hours  USE Initial Service  |   | CLIMATE Mediterranean  CLIMATE Moderate   |
| Multifleet SCD 10W  Change every 250 hours  USE Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 50 hours  USE Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 50 hours  USE Initial service  PRODUCT RECOMMENDATION 1  Kroontrak MTH 10W-30 | PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40 | Tropical  CLIMATE  Mediterranean  CLIMATE |

## FUCHS ARTICULATED LOADERS F1100 YANMAR 3TNV88 (2007-2014)



| use<br>Initial service   | CLIMATE<br>Cold |
|--------------------------|-----------------|
| PRODUCT RECOMMENDATION 1 |                 |
| Multifleet SCD 10W       |                 |
| Change every 50 hours    |                 |

| AXLE FRONT               |                             |          |  |
|--------------------------|-----------------------------|----------|--|
| USE                      |                             | CLIMATE  |  |
| Normal                   |                             | Moderate |  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |  |
| Gearlube GL-5 80W-90     | Unigear HS GL-3/GL-5 80W-90 |          |  |

| AXLE REAR                |                             |          |  |
|--------------------------|-----------------------------|----------|--|
| USE                      |                             | CLIMATE  |  |
| Normal                   |                             | Moderate |  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |  |
| Gearlube GL-5 80W-90     | Unigear HS GL-3/GL-5 80W-90 |          |  |

| TRANSFERBOX              |                             |          |
|--------------------------|-----------------------------|----------|
| USE                      |                             | CLIMATE  |
| Normal                   |                             | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90     | Unigear HS GL-3/GL-5 80W-90 |          |

| HYDRAULIC SYSTEM         |                          |          |  |
|--------------------------|--------------------------|----------|--|
| use<br>Normal            |                          | CLIMATE  |  |
|                          |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |  |
| Perlus Biosynth 46       | Perlus H 46              |          |  |

| COOLING SYSTEM                   |          |  |
|----------------------------------|----------|--|
| USE                              | CLIMATE  |  |
| Normal                           | Moderate |  |
| PRODUCT RECOMMENDATION 1         |          |  |
| Coolant -38 Organic NF           |          |  |
| Change over 1000 hours/12 months | <u>'</u> |  |

Change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

## FUCHS ARTICULATED LOADERS F1100 YANMAR 3TNV88 (2007-2014)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.