FUCHS ARTICULATED LOADERS F1200L YANMAR 3TNV88 (2007-2014)



ENGINE Yanmar 3TNV88 Capacity: 6,7 liter		
JSE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		
Change every 250 hours	'	,
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 250 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Change every 250 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
PRODUCT RECOMMENDATION 1		
PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
Multifleet SCD 10W Change every 250 hours		CLIMATE
Multifleet SCD 10W Change every 250 hours		climate Tropical
PRODUCT RECOMMENDATION 1 Multifleet SCD 10W Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 40		
Multifleet SCD 10W Change every 250 hours use Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours		
Multifleet SCD 10W Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE		ССІМАТЕ
Multifleet SCD 10W Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE Initial service		Tropical
Multifleet SCD 10W Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1		ССІМАТЕ
Multifleet SCD 10W Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30		ССІМАТЕ
Multifleet SCD 10W Change every 250 hours USE Initial Service PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE Initial Service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours		ССІМАТЕ
Multifleet SCD 10W Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours		Tropical CLIMATE Mediterranean CLIMATE
Multifleet SCD 10W Change every 250 hours USE Initial Service PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE Initial Service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE Initial Service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE Initial Service		CLIMATE Mediterranean CLIMATE Moderate
Multifleet SCD 10W Change every 250 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40	Tropical CLIMATE Mediterranean CLIMATE

FUCHS ARTICULATED LOADERS F1200L YANMAR 3TNV88 (2007-2014)



use Initial service	CLIMATE Cold
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 50 hours	

AXLE FRONT			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		

AXLE REAR			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		

TRANSFERBOX		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

HYDRAULIC SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus Biosynth 46	Perlus H 46		

COOLING SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 1000 hours/ 12 months	<u>'</u>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

FUCHS ARTICULATED LOADERS F1200L YANMAR 3TNV88 (2007-2014)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.