FURUKAWA (EUROPE) TRACKED EXCAVATORS 645E



ENGINE Furukawa F.683T		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
	•••••••	

Change every 250 hours

HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 1000 hours	· · ·

Change every 1000 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

FRONT IDLERS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Unigear HS GL-3/GL-5 80W-90	Gearlube GL-5 85W-140

Change every 2000 hours

FURUKAWA (EUROPE) TRACKED EXCAVATORS 645E



TRACK IDLERS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

TRACK ROLLERS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.