GEHL COMPACT TRACKED LOADERS RT/CTL RT210 YANMAR 4TNV98T-ZXNMS TIER 4I (S/N 21041 - 921000) (2012-2013)



ENGINE Yanmar 4TNV98T Capacity: 10,4 liter		
USE		CLIMATE
Normal, fuel sulfur level <0,05%		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40
Change every 250 hours/ 6 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40
Change every 50 hours		

TRAVEL REDUCTION UNITS Capacity: 0,9-1,1 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 1000 hours/ 12 mont	hs	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 150 hours/ 4 months	,	,

HYDRAULIC SYSTEM Capacity: 81,4 liter (Hydraulic system including tank), Capacity: 52,2 liter (Hydraulic tank)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Perlus HCD 46		
Change every 250 hours/ 6 months		
USE	CLIMATE	
Biodegradable oil	Moderate	
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Change every 250 hours/ 6 months		

GEHL COMPACT TRACKED LOADERS RT/CTL RT210 YANMAR 4TNV98T-ZXNMS TIER 4I (S/N 21041 - 921000) (2012-2013)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 14,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.