

GEHL TRACKED EXCAVATORS MB/Z 223

AB00440 - AD04192 (2009-2013)



ENGINE Yanmar 3TNE74
Capacity: 2,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 250 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Change every 50 hours

HYDRAULIC SYSTEM

Capacity: 21 liter (Hydraulic tank), Capacity: 30 liter (System)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

Check every 10 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

Change every 10 hours

COOLING SYSTEM

Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours

GEHL TRACKED EXCAVATORS MB/Z 223

AB00440 - AD04192 (2009-2013)



SLEW RING GEAR TEETH

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Check every 12 months/ 500 hours

TRACK DRIVE GEARBOXES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 50 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.