PRODUCT RECOMMENDATION

# GEHL TRACKED EXCAVATORS MB/Z 223 AE00001 - (2009-2013)

**ENGINE** Yanmar 3TNV76
Capacity: 3,5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Kroontrak MTH 10W-30** | **Synfleet SHPD 10W-40** | **Dieselfleet CD+ 15W-40** |

*Check every 10 hours, change every 250 hours/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Kroontrak MTH 10W-30** | **Synfleet SHPD 10W-40** | **Dieselfleet CD+ 15W-40** |

*Change every 50 hours*

**HYDRAULIC SYSTEM**
Capacity: 21 liter (Hydraulic tank), Capacity: 30 liter (System)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Perlus H 46** | **Perlus AF 46** | |

*Check every 10 hours, change every 1000 hours/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Perlus H 46** | **Perlus AF 46** | |

*Change every 10 hours*

**COOLING SYSTEM**
Capacity: 4 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Coolant SP 15+** | **Coolant SP 12** | **Coolant -38 Organic NF** |

*Check every 10 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# GEHL TRACKED EXCAVATORS MB/Z 223 AE00001 - (2009-2013)

## SLEW RING GEAR TEETH

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **MoS2 Grease EP 2** | | |
| *Check every 12 months/ 500 hours* | | |

## TRACK DRIVE GEARBOXES

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |
| *Check every 50 hours, change every 1000 hours/ 12 months* | | |

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |
| *Change every 500 hours* | | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367