

GEHL TRACKED EXCAVATORS MB/Z 383Z

TIER 3, AG00573-



ENGINE Yanmar 3TNV88
Capacity: 7,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Armado Synth 10W-40

Check every 10 hours, change every 500 hours

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Armado Synth 10W-40

Check every 10 hours, change every 250 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Armado Synth 10W-40

Change every 50 hours

HYDRAULIC SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

Check every 10 hours, change every 500 hours

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 500 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Check every 50 hours

GEHL TRACKED EXCAVATORS MB/Z 383Z

TIER 3, AG00573-



COOLING SYSTEM

Capacity: 5,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 1000 hours

SLEW GEAR RING & PINION

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Check every 50 hours

SWING REDUCTION GEARBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 50 hours, change every 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

TRAVEL REDUCTION UNIT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 50 hours, change every 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

GEHL TRACKED EXCAVATORS MB/Z 383Z TIER 3, AG00573-



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.