PRODUCT RECOMMENDATION

GEHL TRACKED EXCAVATORS MB/Z Z25 YANMAR 3TNV80F-SXNBV TIER 4 (2014 AND AFTER)

ENGINE Yanmar 3TNV80F
Capacity: 5,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Kroontrak MTH 10W-30**	**Multifleet SHPD 15W-40**
Change every 500 hours/ 12 months		

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 500 hours/ 12 months		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Kroontrak MTH 10W-30**	**Multifleet SHPD 15W-40**
Change every 50 hours		

USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 50 hours		

TRAVEL REDUCTION UNITS
Capacity: 0,5 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	
Check every 250 hours, change every 1000 hours/ 12 months		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	
Change every 100 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

GEHL TRACKED EXCAVATORS MB/Z Z25 YANMAR 3TNV80F-SXNBV TIER 4 (2014 AND AFTER)

HYDRAULIC SYSTEM

Capacity: 54 liter (Hydraulic system including tank), Capacity: 36 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Perlus HCD 46		

Change every 1000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

COOLING SYSTEM

Capacity: 3,2 liter (Radiator)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15	**Coolant SP 15+**	**Coolant SP 12**

Change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367