## GENIE GENERATORS T T25G (GGG-19214 - >) KUBOTA V1505-E



| ENGINE Kubota V1505<br>Capacity: 6,7 liter  |                          |                          |  |  |
|---|--------------------------|--------------------------|--|--|
| USE   |                          | CLIMATE                  |  |  |
| Normal                                      |                          | Tropical                 |  |  |
| PRODUCT RECOMMENDATION 1                    |                          |                          |  |  |
| Multifleet SCD 30                           |                          |                          |  |  |
| Check every 10 hours, change every 200 h    | nours                    |                          |  |  |
| USE   |                          | CLIMATE                  |  |  |
| Normal                                      |                          | Mediterranean            |  |  |
| PRODUCT RECOMMENDATION 1                    |                          |                          |  |  |
| Multifleet SCD 20W-20                       |                          |                          |  |  |
| Check every 10 hours, change every 200 h    | nours                    |                          |  |  |
| USE   |                          | CLIMATE                  |  |  |
| Normal                                      |                          | Moderate                 |  |  |
| PRODUCT RECOMMENDATION 1                    | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |  |  |
| Agridiesel CRD+ 15W-40                      | Kroontrak MTH 10W-30     | Synfleet SHPD 10W-40     |  |  |
| Check every 10 hours, change every 200 h    | nours                    |                          |  |  |
| USE   |                          | CLIMATE                  |  |  |
| Normal                                      |                          | Arctic                   |  |  |
| PRODUCT RECOMMENDATION 1                    |                          |                          |  |  |
| Multifleet SCD 10W                          |                          |                          |  |  |
| Check every 10 hours, change every 200 h    | nours                    |                          |  |  |
| USE   |                          | CLIMATE                  |  |  |
| Initial service                             |                          | Tropical                 |  |  |
| PRODUCT RECOMMENDATION 1                    |                          |                          |  |  |
| Multifleet SCD 30                           |                          |                          |  |  |
| Check every 10 hours, change every 50 hours |                          |                          |  |  |
| USE   |                          | CLIMATE                  |  |  |
| Initial service                             |                          | Mediterranean            |  |  |
| PRODUCT RECOMMENDATION 1                    |                          |                          |  |  |
| Multifleet SCD 20W-20                       |                          |                          |  |  |
| Check every 10 hours, change every 50 hours |                          |                          |  |  |
| USE   |                          | CLIMATE                  |  |  |
| Initial service                             |                          | Moderate                 |  |  |
| PRODUCT RECOMMENDATION 1                    | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |  |  |
| Agridiesel CRD+ 15W-40                      | Kroontrak MTH 10W-30     | Synfleet SHPD 10W-40     |  |  |
| o   |                          |                          |  |  |

Check every 10 hours, change every 50 hours

## GENIE GENERATORS T T25G (GGG-19214 - >) KUBOTA V1505-E



| USE                      |  | CLIMATE |  |  |
|--------------------------|--|---------|--|--|
| Initial service          |  | Arctic  |  |  |
| PRODUCT RECOMMENDATION 1 |  |         |  |  |
| Multifleet SCD 10W       |  |         |  |  |
|                          |  |         |  |  |

Check every 10 hours, change every 50 hours

| HYDRAULIC SYSTEM<br>Capacity: 7,6 liter (Hydraulic system including tank), Capacity: 5,3 liter (Hydraulic tank) |                          |                          |  |  |
|---|--------------------------|--------------------------|--|--|
| USE   |                          | CLIMATE                  |  |  |
| Normal  |                          | Moderate                 |  |  |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |  |  |
| Perlus H 46   | Perlus H 32              | Perlus AF 46             |  |  |

Change every 2000 hours/ 24 months

| COOLING SYSTEM<br>Capacity: 4 liter          |                          |          |  |
|--|--------------------------|----------|--|
| USE  |                          | CLIMATE  |  |
| Normal                                       |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1                     | PRODUCT RECOMMENDATION 2 |          |  |
| Coolant -38 Organic NF                       | Coolant -26              |          |  |
| Check every 10 hours, change every 12 months |                          |          |  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.